



**STANDARD FEATURES**

- MOTOR: HR-2
- STD FORCE 8 N  
(CONSULT FACTORY FOR HIGHER FORCE)
- ROTATION: ±5 DEG
- SPEED: 180 DEG/SEC (CONTROLLER DEPENDENT)
- ENCODER RESOLUTION: 0.02 ARC-SEC TO 13 ARC-SEC  
0.02 ARC-SEC USING 4096 INTERPOLATION  
(CONTROLLER DEPENDENT)
- SYSTEM REPEATABILITY: +/- 1 ENCODER COUNT  
(CONTROLLER DEPENDENT)
- HOME SENSOR: STANDARD
- BEARINGS: PRECISION ARCHED CROSS ROLLER
- BEARING DYNAMIC LOAD RATING: 1 kN
- SYSTEM LOAD CAPACITY: APPLICATION DEPENDENT  
PLEASE CONSULT THE FACTORY
- ENCLOSURES: ALUMINUM 6061-T6
- ENVIRONMENT: STANDARD, CLEAN ROOM, VACUUM  
10e-7 TORR, AND VACUUM 10e-10 TORR  
(CONSULT FACTORY)
- TEMPERATURE: 0 to 100 DEG C
- HUMIDITY: 10% to 80% NON-CONDENSING
- ASSEMBLY MASS: 0.86 kg

**ACCESSORIES**

MOTOR AMPLIFIER

**OPTIONAL EQUIPMENT**

MOTION CONTROLLERS

CUSTOM DESIGNS FOR OEM INTEGRATION

ALIO INDUSTRIES PROPRIETARY INFORMATION

11919 W I-70 FRONTAGE ROAD NORTH, UNIT 119, WHEAT RIDGE, CO 80033 USA  
(Tel) 303.339.7500 - SALES@ALIOINDUSTRIES.COM - WWW.ALIOINDUSTRIES.COM

DRAWN				
NBROWN				5/2/2005
CHECKED		TITLE		
		AI-HR2-GONI-064		
Tolerances:		SIZE	DWG NO	
x.x ± .04 in		B	00452	
x.xx ± .02 in				REV
x.xxx ± .005 in				001
MATERIAL		SCALE	REV	
		ALIO STD TEMPLATE - REV 004	SHEET 1 OF 1	