



STANDARD FEATURES

- MOTOR: HR-2
- STD TORQUE 0.08 N-m
(CONSULT FACTORY FOR HIGHER FORCE)
- ROTATION: 360 DEGREES CONTINUOUS
- SPEED: >700 DEG/SEC
- ENCODER RESOLUTION: 0.03 ARC-SEC TO 27 ARC-SEC
0.03 ARC-SEC USING 4096 INTERPOLATION
(CONTROLLER DEPENDENT)
- SYSTEM REPEATABILITY: +/- 1 ENCODER COUNT
(CONTROLLER DEPENDENT)
- HOME SENSOR: STANDARD
- BEARINGS: PRECISION CROSSED ROLLER
- BEARING DYNAMIC LOAD RATING: 6 kN
- SYSTEM LOAD CAPACITY: APPLICATION DEPENDENT
PLEASE CONSULT THE FACTORY
- ENCLOSURES: ALUMINUM 6061-T6
STAINLESS STEEL OPTIONAL
- ENVIRONMENT: STANDARD, CLEANROOM, VACUUM
10e-7 TORR, AND VACUUM 10e-10 TORR
(CONSULT FACTORY)
- TEMPERATURE: 0 to 85 DEG C
- HUMIDITY: 10% to 80% NON-CONDENSING
- ASSEMBLY MASS: 1.4 kg

ACCESSORIES

- MOTOR AMPLIFIER
- ROTATION LIMIT MARKERS

OPTIONAL EQUIPMENT

- MOTION CONTROLLERS

CUSTOM DESIGNS FOR OEM INTEGRATION

ALIO INDUSTRIES PROPRIETARY INFORMATION

11919 W I-70 FRONTAGE ROAD NORTH, UNIT 119, WHEAT RIDGE, CO 80033 USA
(Tel) 303.339.7500 - SALES@ALIOINDUSTRIES.COM - WWW.ALIOINDUSTRIES.COM



DRAWN NBROWN		3/3/2005		TITLE AI-133R	
CHECKED					
Tolerances: x.x ± .04 in x.xx ± .02 in x.xxx ± .005 in				SIZE B	DWG NO 00148
MATERIAL				REV 001	
SCALE				SHEET 1 OF 1	